Programming Paradigms

Lecture 19:

Functional Languages

Prof. Dr. Michael Pradel

Software Lab, University of Stuttgart

Winter 2019/2020

Wake-up Exercise

What does the following Scheme code evaluate to?

```
(let ((a 3))
  (let ((a 4)
        (b a))
    (+ a b)))
```

https://ilias3.uni-stuttgart.de/vote/0ZT9

Wake-up Exercise

What does the following Scheme code evaluate to?

```
(let ((a 3))
  (let ((a 4)
        (b a))
    (+ a b)))
```

Result: 7

https://ilias3.uni-stuttgart.de/vote/0ZT9

Wake-up Exercise

What does the following Scheme code evaluate to?

```
(let ((a 3))
  (let ((a 4)
        (b a))
    (+ a b)))
```

`let` **binds names to values**

Result: 7

https://ilias3.uni-stuttgart.de/vote/0ZT9

Wake-up Exercise

What does the following Scheme code evaluate to?

```
(let ((a 3))
  (let ((a 4)
        (b a))
    (+ a b)))
```

`let` binds names to values

Scope of bindings: Second argument only

Result: 7

https://ilias3.uni-stuttgart.de/vote/0ZT9

Wake-up Exercise

What does the following Scheme code evaluate to?

```
(let ((a 3))
  (let ((a 4)
        (b a))
    (+ a b)))
```

`let` binds names to values

`b` takes the value of the outer `a`

Scope of bindings: Second argument only

Result: 7

https://ilias3.uni-stuttgart.de/vote/0ZT9

Functional Languages

- **Functional paradigm: Alternative to imperative PLs**
  - Output: Mathematical function of input
  - No internal state, no side effects
- **In practice: Fuzzy boundaries**
  - "Functional" features in many "imperative" PLs
    - E.g., higher-order functions
  - "Imperative features" in many "functional" PLs
    - E.g., assignment and iteration

Historical Origins

- **Lambda calculus**
  - Alonzo Church, 1930s
- **Express computation based on**
  - Abstraction into functions
    - E.g., $(\lambda x.M)$
  - Function application
    - E.g., $(M\ N)$

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Functions assigned to variables, passed as arguments, or return values

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Use a function on different kinds of values, e.g., using type inference

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Ideal for recursion (handle first element and then recursively the remainder)

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Functions can return any structured data, e.g., lists and functions

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Construct aggregate objects inline and all-at-once

Features

- First-class function values and higher-order function
- Extensive polymorphism
- List types and operators
- Structured function returns
- Constructors for structured objects
- Garbage collection

Necessary because evaluation tends to create lots of temporary data

Purely Functional PLs

- **Functions depend only on their parameters**
  - Not on any other global or local state
  - Order of evaluation is irrelevant
    - Eager and lazy evaluation yield same result
- **E.g., Haskell**
  - By Philip Wadler et al., first released in 1990
  - Actively used as a research language

Non-Pure Functional PLs

- **Mix of functional features with assignments**
- **E.g., Scheme**
  - Dialect of Lisp
  - By Guy Steele and Gerlad Jay Sussman (MIT)
- **E.g., OCaml**
  - Extends ML with OO features
  - Developed at INRIA (France)

Plan for Today

- **Introduction**
- **A Bit of Scheme** ←
- **Evaluation Order**

Function Application

- **Pair of parentheses: Function application**
  - First expression inside: Function
  - Remaining expressions: Arguments
- **Examples:**

```
(+ 3 4)
```

```
((+ 3 4))
```

Function Application

- **Pair of parentheses: Function application**
  - First expression inside: Function
  - Remaining expressions: Arguments
- **Examples:**

```
(+ 3 4)
```

Applies + function to 3 and 4. Evaluates to 7.

```
((+ 3 4))
```

Function Application

- **Pair of parentheses: Function application**
  - First expression inside: Function
  - Remaining expressions: Arguments
- **Examples:**

```
(+ 3 4)
```

Applies + function to 3 and 4. Evaluates to 7.

```
((+ 3 4))
```

Tries to call 7 with zero arguments. Gives runtime error.

Creating Functions

- **Evaluating a lambda expression yields a function**
  - First argument to `lambda`: Formal parameters
  - Remaining arguments: Body of the function
- **Example:**

```
(lambda (x) (* x x))
```

Creating Functions

- **Evaluating a lambda expression yields a function**
  - First argument to `lambda`: Formal parameters
  - Remaining arguments: Body of the function
- **Example:**

```
(lambda (x) (* x x))
```

Yields the "square" function

Bindings

- **Names bound to values with `let`**
  - First argument: List of name-value pairs
  - Second argument: Expressions to be evaluated in order
- **Example:**

```
(let ((a 3)
      (b 4)
      (square (lambda (x) (* x x)))
      (plus +))
    (sqrt (plus (square a) (square b))))
```

Bindings

- **Names bound to values with `let`**
  - First argument: List of name-value pairs
  - Second argument: Expressions to be evaluated in order
- **Example:**

```
(let ((a 3)
      (b 4)
      (square (lambda (x) (* x x)))
      (plus +))
    (sqrt (plus (square a) (square b))))
```

Yields 5.0

Conditional Expressions

- **Simple conditional expression with `if`**
  - First argument: Condition
  - Second/third argument: Value returned if condition is true/false
- **Multiway conditional expression with `cond`**
- **Examples:**

```
(if (< 2 3) 4 5)
```

```
(cond
  ((< 3 2) 1)
  ((< 4 3) 2)
  (else 3))
```

Conditional Expressions

- **Simple conditional expression with `if`**
  - First argument: Condition
  - Second/third argument: Value returned if condition is true/false
- **Multiway conditional expression with `cond`**
- **Examples:**

```
(if (< 2 3) 4 5)
```

Yields 4

```
(cond
  ((< 3 2) 1)
  ((< 4 3) 2)
  (else 3))
```

Conditional Expressions

- **Simple conditional expression with `if`**
  - First argument: Condition
  - Second/third argument: Value returned if condition is true/false
- **Multiway conditional expression with `cond`**
- **Examples:**

```
(if (< 2 3) 4 5)
```

Yields 4

Yields 3

```
(cond
  ((< 3 2) 1)
  ((< 4 3) 2)
  (else 3))
```

Dynamic Typing

- **Types are determined and checked at runtime**
- **Examples:**

```
(if (> a 0) (+ 2 3) (+ 2 "foo"))
```

```
(define min (lambda (a b) (if (< a b ) a b)))
```

Dynamic Typing

- **Types are determined and checked at runtime**
- **Examples:**

```
(if (> a 0) (+ 2 3) (+ 2 "foo"))
```

Evaluates to 5 if `a` is positive; runtime type error otherwise.

```
(define min (lambda (a b) (if (< a b ) a b)))
```

Dynamic Typing

- **Types are determined and checked at runtime**
- **Examples:**

```
(if (> a 0) (+ 2 3) (+ 2 "foo"))
```

Evaluates to 5 if `a` is positive; runtime type error otherwise.

```
(define min (lambda (a b) (if (< a b ) a b)))
```

Implicitly polymorphic: Works both for integers and floats.

Quiz: Functions in Scheme

Which of the following yields 9?

```
; Program 1
((lambda (x) (* x x)) 3)

; Program 2
(- (+ 12 3) (+ 2 4))

; Program 3
(9)

; Program 4
((lambda (x y) (- x y)) (+ 10 0) (- 4 2))
```

https://ilias3.uni-stuttgart.de/vote/0ZT9

Quiz: Functions in Scheme

Which of the following yields 9?

```
; Program 1
((lambda (x) (* x x)) 3) ✔

; Program 2
(- (+ 12 3) (+ 2 4)) ✔

; Program 3
(9) ✘

; Program 4
((lambda (x y) (- x y)) (+ 10 0) (- 4 2)) ✘
```

https://ilias3.uni-stuttgart.de/vote/0ZT9

Lists

- **Central data structure with various operations**
  - `car` extracts first element
  - `cdr` extracts all elements but first
  - `cons` joins a head to the rest of a list
- **Examples:**

```
(car '(2 3 4))      (cdr '(2 3 4))      (cons 2 '(3 4))
```

Lists

- **Central data structure with various operations**
  - `car` extracts first element
  - `cdr` extracts all elements but first
  - `cons` joins a head to the rest of a list
- **Examples:**

"Quote" to prevent interpreter from evaluating (i.e., a literal)

```
(car '(2 3 4))     (cdr '(2 3 4))     (cons 2 '(3 4))
```

Lists

- **Central data structure with various operations**
  - `car` extracts first element
  - `cdr` extracts all elements but first
  - `cons` joins a head to the rest of a list
- **Examples:**

"Quote" to prevent interpreter from evaluating (i.e., a literal)

```
(car '(2 3 4))      (cdr '(2 3 4))      (cons 2 '(3 4))
```

Yields 2

Lists

- **Central data structure with various operations**
  - `car` extracts first element
  - `cdr` extracts all elements but first
  - `cons` joins a head to the rest of a list
- **Examples:**

"Quote" to prevent interpreter from evaluating (i.e., a literal)

```
(car '(2 3 4))      (cdr '(2 3 4))      (cons 2 '(3 4))
```

Yields 2 **Yields (3 4)**

Lists

- **Central data structure with various operations**
  - `car` extracts first element
  - `cdr` extracts all elements but first
  - `cons` joins a head to the rest of a list
- **Examples:**

"Quote" to prevent interpreter from evaluating (i.e., a literal)

```
(car '(2 3 4))
```

Yields 2

```
(cdr '(2 3 4))
```

Yields (3 4)

```
(cons 2 '(3 4))
```

Yields (2 3 4)

Assignments

- **Side effects via**
  - `set!` for assignment to variables
  - `set-car!` for assigning head of list
  - `set-cdr!` for assigning tail of list
- **Example:**

```
(let ((x 2)
      (l '(a b)))
  (set! x 3)
  (set-car! l '(c d))
  (set-cdr! l '(e))
  (cons x l))
```

Assignments

- **Side effects via**
  - `set!` for assignment to variables
  - `set-car!` for assigning head of list
  - `set-cdr!` for assigning tail of list
- **Example:**

```
(let ((x 2)
      (l '(a b)))
  (set! x 3)
  (set-car! l '(c d))
  (set-cdr! l '(e))
  (cons x l))
```

Yields (3 (c d) e)

Sequencing

- Cause interpreter to evaluate multiple expressions one after another with `begin`
- Example:

```
(let
    ((n "there"))
  (begin
    (display "hi ")
    (display n)))
```

Sequencing

- Cause interpreter to evaluate multiple expressions one after another with `begin`
- Example:

```
(let
    ((n "there"))
  (begin
    (display "hi ")
    (display n)))
```

Prints ”hi there”

Iteration

- Several forms of loops, e.g., with `do`
- Example:

```
((lambda (n)
  (do ((i 0 (+ i 1))
       (a 0 b)
       (b 1 (+ a b)))
    ((= i n) b)
    (display b)
    (display " ")))) 5)
```

Iteration

- **Several forms of loops, e.g., with `do`**
- **Example:**

```
((lambda (n)
  (do ((i 0 (+ i 1))
       (a 0 b)
       (b 1 (+ a b)))
    ((= i n) b)
    (display b)
    (display " ))) 5)
```

List of triples that each

- specify a new variable
- its initial value
- expression to compute next value

Iteration

- **Several forms of loops, e.g., with `do`**
- **Example:**

```
((lambda (n)
  (do ((i 0 (+ i 1))
       (a 0 b)
       (b 1 (+ a b)))
      ((= i n) b)
      (display b)
      (display " ))) 5)
```

List of triples that each

- specify a new variable
- its initial value
- expression to compute next value

Termination condition and expression to be returned

Iteration

- **Several forms of loops, e.g., with `do`**
- **Example:**

```
((lambda (n)
  (do ((i 0 (+ i 1))
       (a 0 b)
       (b 1 (+ a b)))
    ((= i n) b)
    (display b)
    (display " "))) 5)
```

List of triples that each

- specify a new variable
- its initial value
- expression to compute next value

Termination condition and expression to be returned

Body of the loop

Iteration

- Several forms of loops, e.g., with `do`
- Example:

```
((lambda (n)
  (do ((i 0 (+ i 1))
       (a 0 b)
       (b 1 (+ a b)))
      ((= i n) b)
      (display b)
      (display " ")) 5)
```

List of triples that each

- specify a new variable
- its initial value
- expression to compute next value

Termination condition and expression to be returned

Body of the loop

Computes first n Fibonacci numbers

Programs as Lists

- **Programs and lists: Same syntax**
  - Both are S-expressions: String of symbols with balanced parentheses
- **Construct and manipulate an unevaluated program as a list**
- **Evaluate with `eval`**
- **Example:**

```
(eval (cons '+ (list '2 '3)))
```

Programs as Lists

- **Programs and lists: Same syntax**
  - Both are S-expressions: String of symbols with balanced parentheses
- **Construct and manipulate an unevaluated program as a list**
- **Evaluate with `eval`**
- **Example:**

```
(eval (cons '+ (list '2 '3)))
```

Constructs a list from the given arguments

Programs as Lists

- **Programs and lists: Same syntax**
  - Both are S-expressions: String of symbols with balanced parentheses
- **Construct and manipulate an unevaluated program as a list**
- **Evaluate with `eval`**
- **Example:**

```
(eval (cons '+ (list '2 '3)))
```

Constructs a list from the given arguments

Yields 5

Plan for Today

- **Introduction**
- **A Bit of Scheme**
- **Evaluation Order** ←

Evaluation Order

- **In what order to evaluate subcomponents of an expression?**
  - Applicative-order: Evaluate arguments before passing them to the function
  - Normal-order: Pass arguments unevaluated and evaluate once used

```
(define double (lambda (x) (+ x x)))
```

Applicative-order

```
  double (* 3 4)
⇒ double 12
⇒ + 12 12
⇒ 24
```

Normal-order

```
  double (* 3 4)
⇒ + (* 3 4) (* 3 4)
⇒ + 12 (* 3 4)
⇒ + 12 12
⇒ 24
```

Doing extra work with normal-order

```
(define switch (lambda (x a b c)
    (cond ((< x 0) a)
          ((= x 0) b)
          ((> x 0) c))))
```

→ Doing extra work in applicative order

Applicative-order

```
(switch -1 (+ 1 2) (+ 2 3) (+ 3 4))
⇒ (switch -1 3 (+ 2 3) (+ 3 4))
⇒ (switch -1 3 5 (+ 3 4))
⇒ (switch -1 3 5 7)
⇒ (cond ((< -1 0) 3)
        ((= -1 0) 5)
        ((> -1 0) 7))
⇒ (cond (#t 3)
        ⋮ )
⇒ 3
```

Normal-order

```
(switch -1 (+ 1 2) (+ 2 3) (+ 3 4))
⇒ (cond ((< -1 0) (+ 1 2))
        ((= -1 0) (+ 2 3))
        ((> -1 0) (+ 3 4)))
⇒ (cond (#t (+ 1 2)
        ⋮ )
⇒ (+ 1 2)
⇒ 3
```

Impact on Correctness

- **Evaluation order also affects correctness**
- **E.g., runtime error when evaluating an ”unneeded” subexpression**
  - Terminates program in applicative-order
  - Not noticed in normal-order

Lazy Evaluation

- **Evaluate subexpressions on-demand**
- **Avoid re-evaluating the same expression**
  - Memorize its result
- **Transparent to programmer only in PL without side effects, e.g., Haskell**
  - In PLs with side effects, e.g., Scheme: Programmer can explicitly ask for lazy evaluation with `delay`

Quiz: Evaluation Order

```
(define double (lambda (x) (+ x x)))
(define avg (lambda (x y) (/(+ x y) 2)))
```

How many evaluation steps are needed to evaluate

```
(double(avg 2 4))
```

under applicative-order and normal-order evaluation?

https://ilias3.uni-stuttgart.de/vote/0ZT9

Quiz: Evaluation Order

```
(define double (lambda (x) (+ x x)))
(define avg (lambda (x y) (/(+ x y) 2)))
```

How many evaluation steps are needed to evaluate

```
(double(avg 2 4))
```

under applicative-order and normal-order evaluation?

5 and 8

https://ilias3.uni-stuttgart.de/vote/0ZT9

Applicative-order

```
(double (avg 2 4))
=> (double (/ (+ 2 4) 2))
=> (double (/ 6 2))
=> (double 3)
=> (+ 3 3)
=> 6
```

5 steps

Normal-order

```
(double (avg 2 4))
=> (+ (avg 2 4) (avg 2 4))
=> (+ (/ (+ 2 4) 2) (avg 2 4))
=> (+ (/ 6 2) (avg 2 4))
=> (+ 3 (avg 2 4))
=> (+ 3 (/ (+2 4) 2))
=> (+ 3 (/ 6 2))
=> (+ 3 3)
=> 6
```

8 steps

Plan for Today

- **Introduction**
- **A Bit of Scheme**
- **Evaluation Order** ✔